

TITLE OF THE INVENTION

INVERTED MICROSCOPE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Applications No. 2000-285637, filed September 20, 2000;
and No. 2001-119900, filed April 18, 2001, the entire
contents of both of which are incorporated herein by
reference.

10 BACKGROUND OF THE INVENTION

1. Field of the Invention

15 The present invention relates to an inverted
microscope for magnifying and observing a sample placed
on a stage by objective lenses arranged directly below
the stage.

2. Description of the Related Art

Microscope photographing devices are widely
employed for recording applications in research
activities of respective fields handling living cells
20 in medical science and physiology, research and testing
activities in industrial fields to observe structures
of various metallurgical materials, and to detect
faults and contents thereof, and the like. Still at
present when electronic imaging technologies in digital
25 cameras and the like are spreading, microscope
photographing devices, wherein a large film size
camera, a 35 mm film camera, or both of them are

arranged at the same time, and exposure photographing is carried out onto at least either a large size film or a 35 mm film, are frequently employed in inspection departments and the like of metallurgical materials and the like where photographing is the objective itself.

As one of microscopes using these photographing devices, for examples, in Japanese Patent Application KOKAI Publication No. 63-138314 and Japanese Patent Application KOKOKU Publication No. 57-37848, disclosed are inverted microscopes integrating photographing devices, therein arranged is a configuration that enables exposure photographing onto at least either a large size film or a 35 mm film.

In such inverted microscopes integrating photographing devices (not shown in the above publications), an electromagnetic shutter for releasing is arranged in the front of a position where an image forming light flux is polarized onto a large size film and a 35 mm film, and by opening and closing the above electromagnetic shutter, it is possible to carry out exposure onto the large size film and the 35 mm film.

In recent years, along with the progress of electronic imaging technologies, high precision digital images may be handled easily, and digital cameras are assembled into many optical microscopes. In the case when such a digital camera is assembled into an inverted microscope, the digital camera is arranged

through a TV camera photographing lens onto a top port of a trinocular observation tube, or the digital camera is arranged onto a side port through the same TV camera photographing lens.

5 On the other hand, apart from the applications for recording images by use of several type of a camera, there are applications for observing magnified images of samples by placing an obscure glass (so-called a screen device) at an attached position of a large
10 size film camera.

In this case, an observer removes a large size film camera first, and attaches a screen device (not illustrated) provided with an obscure glass in the place.

15 In the practical observation of a sample image by the screen device, since the attachment position is originally the attachment position of a large size film camera, by setting the shutter in manual operation mode
20 and setting it always opened, a sample image may be displayed on the screen. So as to display clearer images, some devices are equipped with also a hood for blocking light from the external at the external circumference of the screen.

25 Recently, there is a demand in markets for replacing the observation work by looking into eyepieces with the observation work by use of monitor devices such as LCD or the like.

The observation work through eyepieces, wherein an observer must keep a same rigid posture for long hours, will cause fatigue on the observer. Since it is impossible for plural observers to carry observation, there are cases where a device to enable eyepiece observation by plural observers, what is called a discussion device, is additionally installed, or a special TV camera and a monitor are arranged solely for observation by plural observers.

However, in photographing magnified images of an observation sample by a TV camera or a digital camera, when photographing is carried out at the side port, it is impossible to photograph a scale and the like to be inserted into the position of a primary image.

Accordingly, in order to avoid this problem, there is a method of arranging a TV camera or a digital camera onto a top port of a trinocular observation tube through a TV camera photographing lens. However, in this case, a TV camera or a digital camera is positioned in the front of an observer, the observer must displace his posture laterally when to confirm a sample directly by visual inspection, which causes fatigue on the observer and is not preferable accordingly.

Further, when photographing is not carried out by a large size film camera or a 35 mm film camera etc., to those observers, since unnecessary functions are

provided to a microscope main body, the large size film camera or the 35 mm film camera is not only useless, but also leads to increased costs, which has been a problem in the prior art.

5 When to carry out observation by use of
an external monitor or a monitor to be connected with
a personal computer, there are many cases where the
magnification of an observation image to be displayed
cannot be grasped. Especially in observation and
10 records of metallurgical structures, in many cases,
observations is conducted by photographing of a large
size film or a 35 mm film or screen, so the point that
the magnification of an observed image cannot be
grasped directly at field has been a problem in many
15 cases.

 In a microscope in which a photographing device
is incorporated as described in Japanese Patent
Application KOKAI Publication No. 63-138314, since
an electromagnetic shutter is not arranged just before
20 a large size film surface of a large size film camera
portion, or just before a 35 mm film surface of a 35 mm
film camera, and the space of the large size film
camera portion and the space of the 35 mm film camera
are connected with the space of a photographing device
25 portion, it is required to take countermeasures against
stray light so that unnecessary stray light in the
inside of photographing device should not reach to each

film surface.

5 A large size film camera normally has a light
blocking plate that is manually operated just before
a large size film surface, and before a microscope
operator photographing to a large size film, this light
blocking plate is retreated manually from light path,
and after completion of photographing, the light
blocking plate is placed back to its original position
so that the film should not be exposed to light once
10 again.

However, a 35 mm film camera does not have this
light blocking plate, and when a 35 mm film camera is
attached to a photographing device, a shutter in the
35 mm film camera is opened automatically, or a 35 mm
15 film camera initially is not equipped with a shutter,
therefore, it is necessary to conduct countermeasures
against light leakage especially to a 35 mm film.

On the other hand, the above Japanese Patent
Application KOKAI Publication No. 63-138314 (or
20 Japanese Patent Application KOKOKU Publication
No. 57-37848) does not describe the contents on the
above technology, therefore its details are not clear.

In practical applications, in the microscope
having incorporated a photographing device therein as
mentioned above, a light path switching mechanism is
25 devised so as to lead an image forming light flux to
a large size film surface and a 35 mm film surface, and

a switching stroke of a light path switching block is made large, or a 35 mm film camera and the light path switching mechanism are separately blocked with a cylindrical light blocking member so that image forming light flux should not be guided to both the large size film surface and the 35 mm film surface.

Further, it is experimentally verified whether these countermeasures can actually and completely prevent light from leaking or not, and in the case where blocking light is incomplete, various parts to block light are employed in the inside space of a photographing device, which requires a large amount of costs and time in most cases, which has been a problem seen in the prior art.

Further, the above countermeasures against light leakage are effective only when both a large size film camera and a 35 mm film camera are attached to a photographing device in correct manners, therefore, for example, if a large size film camera is removed from a photographing device, there is a fear that a 35 mm film may be exposed to light coming in from the outside, as a consequence, they are not complete countermeasures, which has been another problem with the prior art known well by those skilled in the art.

On the other hand, the above light path switching mechanism for guiding the above image forming light flux to the large size film surface and the 35 mm film

surface is normally operated manually, therefore, if its light path switching block is not at a right switching position but at a central position, part of image forming light flux will not be projected correctly onto a film surface, which is called phenomenon of eclipse, and this phenomenon has been still another nonconformity with the prior art.

BRIEF SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide an inverted microscope that enables efficient combinations of effective image recording devices, and enables to carry out monitor observation and image recording without eyepieces.

Another object of the present invention is to provide an inverted microscope that enables to attach a large size film camera and a camera such as a 35 mm film camera thereto at the same time, and to precisely prevent light leakage to the other camera in the status where one camera is not attached thereto, and to prevent a mistake in photographing owing to light path switching operation.

The inverted microscope according to the present invention is characterized by comprising: an image output port that forms an image of an observation sample to the external surface facing to an observer, at the front side of a microscope main body, below an observation tube to which eyepieces are attached,

wherein photographing devices configured that one of at least two kinds of photographing devices is selectively attachable/detachable to the image output port.

Further, the inverted microscope according to the present invention is characterized in that the at least two kinds of photographing devices include: a photographing device that exposes and forms the image of the observation sample onto a film surface thereof; a TV camera that photographs the image of the observation sample by a photographing element thereof and outputs image data thereof; and a digital camera device that photographs the image of the observation sample and can record the image data as a still image into a recording medium..

The inverted microscope according to the present invention is characterized comprising: an image forming optical system including objective lenses arranged below an observation sample placed on a stage of a microscope main body; an optical element which forms an image of the observation sample at the position where an image forming light flux obtained by the image forming optical system is polarized to an observer side from the optical axis of the objective lens; photographing means for photographing an image of the observation sample; an image recording section configured to record image signals photographed by the photographing means; and display means attached

to the surface facing to the observer at the front of the microscope main body, for displaying images photographed by the photographing means.

Additional objects and advantages of the invention
5 will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and
10 combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention, and together
15 with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a figure showing an outline configuration of a first embodiment according to the present
20 invention;

FIGS. 2A and 2B are figures showing an outline configuration of the first embodiment according to the present invention, wherein a photographing device is incorporated;

25 FIG. 3 is a figure showing an outline configuration of the first embodiment according to the present invention, wherein a digital camera device is

incorporated;

FIG. 4 is a figure showing an outline configuration of the first embodiment according to the present invention, wherein a TV camera is incorporated;

5 FIG. 5 is a figure showing an outline configuration of a second embodiment according to the present invention;

10 FIG. 6 is a figure showing an outline configuration of a third embodiment according to the present invention;

FIGS. 7A and 7B are diagrams showing an outline configuration of a modification of the second embodiment according to the present invention;

15 FIGS. 8A and 8B are diagrams showing an outline configuration of a modification of the second embodiment;

FIGS. 9A and 9B are schematic diagrams showing a configuration of an inverted microscope as a fourth embodiment according to the present invention;

20 FIGS. 10A through 10D are diagrams showing photographing lenses for 3 image recording devices, i.e., a photographing device to which a large size film camera and a 35 mm film camera can be attached, a digital camera device that enables moving image
25 observation by a display device such as LCD or the like built therein, and a TV camera;

FIGS. 11A through 11C are diagrams showing the

shape of an attachment portion of a photographing device or a digital camera device;

FIGS. 12A and 12B are diagrams showing a status wherein the photographing lens and the photographing device of FIG. 10A are attached to the front port of a scope body, and a status wherein the photographing lens and the TV camera 37 of FIG. 10C are attached thereto;

FIG. 13 is a table showing magnifications of a photographing lens for observation with the same magnification as that of eyepieces in a display device such as LCD or the like (magnification of 10);

FIG. 14 is a diagram for explaining a fifth embodiment of the present invention;

FIG. 15 is a diagram for explaining a sixth embodiment of the present invention;

FIG. 16 is a cross sectional view of a microscope photographing device to be applied to an inverted microscope according to a seventh embodiment of the present invention;

FIG. 17 is a view showing a condition for photographing by a large size film camera of the microscope photographing device to be applied to the inverted microscope according to the seventh embodiment;

FIG. 18 is a view showing a condition for photographing by a 35 mm film camera of the microscope photographing device to be applied to the inverted

microscope according to the seventh embodiment;

FIG. 19 is a diagonal appearance viewed from the direction G in FIG. 16 to the direction of a mechanical shutter;

5 FIG. 20 is a view of a second throttle plate viewed from the direction G;

FIGS. 21A through 21D are diagrams showing actions of a mechanical shutter in one embodiment of a microscope photographing device according to the present invention;

10 FIGS. 22A and 22B are diagrams showing positional relations between 2 position sensors and a light path switching block in one embodiment of a microscope photographing device according to the present invention; and

15 FIG. 23 is a block diagram showing a configuration of an electric system in one embodiment of a microscope photographing device according to the present invention.

20 DETAILED DESCRIPTION OF THE INVENTION

The invention is illustrated in more details by reference to the following referential examples and preferred embodiments.

25 FIG. 1 is a figure showing an outline configuration of an inverted microscope to which a first embodiment according to the present invention is applied. FIG. 2A and FIG. 2B are structural diagrams

in case of a photographing device that enables to attach a large size film camera and a 35 mm film camera to the inverted microscope of FIG. 1 is incorporated. FIG. 3 is a structural diagram showing a combination of the inverted microscope of FIG. 1 and a digital camera device that enables moving image observation by a display device such as LCD or the like built therein. FIG. 4 is a figure showing a combination of the inverted microscope of FIG. 1 and a TV camera.

In FIG. 1, at the top of a microscope main body (hereafter referred to as scope body) 1, arranged is a stage 3. On this stage 3, placed is an observation sample 2. Light flux from a light source device 4 by halogen lamp and the like is guided to the scope body 1 via a light projection tube 5, and then reflected by a half mirror 8, and then radiated via an objective lens 6 onto the observation sample 2. In this case, plural objective lenses 6 are held by a revolver 7 and are selectively placed in light path. The light reflected from the observation sample 2 penetrates the half mirror 8 through the objective lens 6, and an magnified image of the observation sample 2 is formed by a tube lens 9 together with the objective lens 6, and then polarized in the horizontal direction by a reflection mirror 10, and thereby a primary image 11 of the observation sample 2 is formed.

By the way, a scale and the like 12 may be

inserted into the position of this primary image 11
for measuring partial size of an observation sample.

Further, the above primary image 11 goes through a
zoom optical system 13, and then is selectively guided
5 into 2 light fluxes, i.e., a reflected light toward the
vertically upside and a permeable light to the forward
by a mirror 14 that may be inserted into and removed
from the light path. The reflection light that is
reflected to the vertically upside forms a secondary
10 image I2, and further is relayed by a relay optical
system 15, and then goes into an eyepiece 17 arranged
at the observation tube 16, and reaches at the eye of
an observer, then is observed by observer. On the
other hand, the permeable light to the forward
15 direction forms a secondary image I2' at the position
protruded by a specified distance from a front port
18 arranged at the front bottom of the scope body 1.
To this front port 18, an image recording device to
be described later herein may be provided in an
20 attachable/detachable manner.

By the way, in FIG. 1, also illustrated are
a split prism 51 that branches the light flux in the
horizontal direction (paper sheet vertical direction)
just below a tube lens 9, a side port 52 that
25 photographs the light flux branched by the split prism
51 by use of a TV camera and the like, and a focusing
handle 11 that drives the revolver 7 holding plural

objective lenses 6 upward and downward, and thereby changes the relative distance between the observation sample 2 on the stage 3 and the objective lens 6, then thereby sets focus on the observation sample 2.

5 Next, a configuration in case where a photographing device to which a large size film camera and a 35 mm film camera may be attached is incorporated into the inverted microscope described in FIG. 1 is explained in reference to FIG. 2A and FIG. 2B.

10 In FIG. 2A and FIG. 2B, identical codes are placed to the same parts as in FIG. 1, and their detailed explanations are omitted herein.

15 In this case, the scope body 1, the stage 3 arranged on the scope body 1, the light source device 4, the light projection tube 5, the objective lens 6, the observation tube 16, eyepieces 17 and the like are identical with those in FIG. 1, therefore, their detailed explanations are omitted herein.

20 In a configuration shown in FIG. 2A and FIG. 2B, a photographing device 19 having a shape to cover the entire front of the scope body 1 is arranged at the front port 18. A large size film camera 20 that enables photographing in large size films such as 4 inches \times 5 inches, 4-1/4 inches \times 3-1/4 inches, and the like is attached to this front side of the photographing device 19, while a 35 mm film camera 21 (not illustrated) that enables photographing in 35 mm

25

films is attached to the side of the photographing device 19.

Inside of the photographing device 19, two kinds of photographing lenses 22 and 23 that may be inserted into and removed from the light path from the front port 18 are arranged. The photographing lens 22 is one for the large size film camera 20, while the photographing lens 23 is one for the 35 mm film camera 21. The large size film camera photographing lens 22 and a reflection mirror 24 are configured as a body, while the 35 mm film camera photographing lens 23 and a reflection mirror 25 are configured as a body. The photographing lens 22 and the reflection mirror 24, or the photographing lens 23 and the reflection mirror 25 are selectively arranged in the light path, an image of an observation sample is formed selectively on the respective film surfaces of the large size film camera 20 and the 35 mm film camera 21 respectively arranged on the front surface and the side surface of the photographing device 19. The light flux reflected by the reflection mirror 24 through the photographing lens 22 is further reflected by two reflection mirrors 26 and 27, and then reaches at the large size film camera 20. Accordingly, in this photographing device 19, the light flux going toward the large size film camera 20 is reflected 3 times in total and forms an image. The light flux reflected by the reflection

mirror 25 through the photographing lens 23 reaches at the 35 mm film camera 21 as it is. Accordingly, in this photographing device 19, the light flux going toward the 35 mm film camera 21 is reflected only once and forms an image.

By the way, a photo frame 28 showing an area photographed by the large size film camera 20 and 35 mm film camera 21 may be inserted into the position of the above secondary image I2.

Next, actions in the actual photographing operation in an inverted microscope with such a photographing device 19 built therein will be explained.

First, the mirror 14 in the scope body 1 is inserted into the light path to prepare a status wherein a sample can be observed by eyepieces. Thereafter, the revolver 7 is turned and an objective lens 6a of low magnification is selected, then the focusing handle 11 is turned and focus is set onto the observation sample 2. Then, the revolver 7 is turned to switch to an objective lens 6b of high magnification, and if the focus is blurred, then the focusing handle 11 is turned a bit to set the focus precisely. When to change observation positions, the XY handle (not shown in the figure) of the stage 3 is operated, and the position of the observation sample 2 is moved, and the desired observation position is moved within the sight of the objective lens 6b.

Next, the photo frame 28 for showing the area photographed by the there large size film camera 20 and the 35 mm film camera 21 is inserted into the position of the secondary image I2, and the area to be taken in by the there large size film camera 20 or the 35 mm film camera 21 is checked. If the area to be taken in is good, then the mirror 14 in the scope body 1 is retreated from the light path, and passage light is supplied to the photographing device 19, and then exposure operation of the photographing device 19 is carried out, and photographing is complete.

Next, in reference to FIG. 3, explained is a configuration where a digital camera that enables moving image observation by use of its built-in display device such as LCD or the like is assembled into the inverted microscope described in reference to FIG. 1. In FIG. 3, identical codes are placed to identical components in FIG. 1, and their detailed explanations are omitted herein.

In this case, the scope body 1, the stage 3 arranged on the scope body 1, the light source device 4, the light projection tube 5, the objective lens 6, the observation tube 16, eyepieces 17 and the like are identical with those in FIG. 1, therefore, their detailed explanations are omitted herein.

In a configuration shown in FIG. 3, a digital camera device 29 having a shape to cover the entire

front of the scope body 1 is arranged at the front port 18. At the frontal top of this digital camera device 29, embedded is a display device 30 such as LCD or the like as display means, while at the frontal bottom, arranged is an operating portion 31 that sends various instructions to the digital camera device 29 itself.

Inside of the digital camera device 29, there are arranged a photographing lens 32 for contracting the light flux incoming from the front port 18 of the scope body 1 and forming an image, and a CCD 33 for outputting the light that has formed an image by the photographing lens 32 as visual signal. An image recording portion 35 to which an internal memory or an MO (magnetic optical disk) and smart media and the like as a recording medium are attachable, the above display device 30 such as LCD or the like, and the operating portion 31 are connected to a signal processing portion 34 that is connected with the CCD 33 and processes output from the CCD 33, respectively.

Next, actions in the actual observation and recording operation in an inverted microscope with such a digital camera device 29 built therein will be explained.

First, the mirror 14 in the scope body 1 is retreated from the light path, and light is supplied to the digital camera device 29. By manipulating the operating portion 31, preview mode (moving image

observation mode) is set, and an image is displayed
onto the display device 30 such as an LCD or so.
Thereafter, the revolver 7 is turned and an objective
lens 6a of low magnification is selected, then the
5 focusing handle 11 is turned and focus is set onto the
image displayed on the display device 30 such as an LCD
or so. Then, the revolver 7 is turned to switch to
an objective lens 6b of high magnification, and if the
focus is blurred, then the focusing handle 11 is turned
10 a bit to set the focus precisely. When to change
observation positions, the XY handle (not shown in the
figure) of the stage 3 is operated, and the position of
the observation sample 2 is moved in an XY direction,
and the desired observation position is moved within
15 the sight of the objective lens 6b.

Next, when recording images into a recording
medium such as an MO or smart media and the like, by
manipulation at the operating portion 31, the mode
is switched from preview mode into recording mode.
20 Thereby, and by photographing operation at the
operating portion 31, an instruction for image
recording is output to the signal processing portion
34, which in turn records the image data accumulated by
the CCD 33 to the image recording portion 35, and
25 actions are complete. By the way, at completion of the
image recording actions, the mode is changed into
preview mode automatically, and the current image is

displayed on the display device 30 such as LCD or the like in real time manner.

Next, in reference to FIG. 4, a configuration in the case where the inverted microscope mentioned in reference to FIG. 1 is combined with a TV camera and a monitor will be explained. In FIG. 4, identical codes are placed to identical components in FIG. 1, and their detailed explanations are omitted herein.

In this case, the scope body 1, the stage 3 arranged on the scope body 1, the light source device 4, the light projection tube 5, the objective lens 6, the observation tube 16, eyepieces 17 and the like are identical with those in FIG. 1, therefore, their detailed explanations are omitted herein.

In a configuration shown in FIG. 4, a TV adapter 36 having a photographing lens therein is arranged at the front port 18. A TV camera 37 having a photographing element such as a CCD or the like is attached to this TV adapter 36. An output signal from the TV camera 37 is processed by a camera control unit 38, and output to an external monitor 39. The images to be observed by this external monitor 39 may be recorded by use of a publicly known video printer (not illustrated herein) and the like, however, explanations on the actions thereof are omitted here.

As mentioned heretofore, in the inverted microscope as the first embodiment according to the

present invention, an image recording device is not installed in the microscope main body, while a secondary image I2 of an observation sample is formed at the position protruded by a specified distance from the front port 18. To this front port 18, 3 image recording devices, namely, a photographing device 19 to which a large size film camera and a 35 mm film camera may be loaded, a digital camera device 29 that enables moving image observation by use of a built-in display device such as an LCD or so, and a TV camera 37, may be selectively attached or detached from. Therefore, it is possible to configure a system according to observer's desired applications. Further, a special photographing lens is arranged in each image recording device, it is possible to realize the optimized magnification for each medium of a large size film, a 35 mm film, CCD, and the like. The optimized magnification herein is defined as, for example, a magnification that realizes a wide photographing (image forming) area almost equal to the observation area by eyepieces.

The secondary image of a sample is set so as to be input into an image recording device, and a zoom optical system is arranged between the primary image of observation sample and the secondary image thereof. As a consequence, an advantage has been made that it is possible to take a scale for measuring partial size of

an observation sample into all the image recording devices that may be attached onto the front port. Further another advantage has been made that it is possible to project magnification converted images by a zoom optical system.

5 The light from the observation sample is reflected once by the reflection mirror 10 in the scope body 1, and then reflected three times to a large size film camera by the photographing device 19, while it is reflected once to a 35 mm film camera, and an image that is reflected even number times in total is photographed. Accordingly, it is possible to photograph a front image. The number of reflections toward the eyepieces 17 is set as minimum as possible, 10 it is possible to attain a preferable observation without deterioration in brightness of an observation image and image quality. Namely, it is possible to restrict the light amount loss by reflection of an image forming light flux in the microscope main body, 15 (scope body) and the deterioration of image quality to the minimum, and to make an image that is formed on the film surface of a large size film camera and a 35 mm film camera a front image (an image in the same direction as that where the sample surface is 20 observed), as a consequence, it is possible to precisely record magnified images of structures of metal or so. 25

When to add another unit of TV camera or digital camera after attaching these image recording devices to the front port 18, it is possible to attach such an additional unit to the side port 52 via an TV adapter 36, which increased the expandability of a system.

By the way, the display device such as LCD or the like to be assembled in a digital camera device may be a plasma display, or a CRT, and any TV camera that has other element such as a CMD element or the like than a CDD may be well employed.

FIG. 5 is a figure showing an outline configuration of an inverted microscope as the second embodiment according to the present invention.

In FIG. 5, a stage 203 is arranged at the top of a microscope main body (hereafter referred to as scope body) 201. An observation sample 202 is placed on this stage 203. Light flux from a light source device 204 by halogen lamp and the like is guided to the scope body 201 via a light projection tube 205. The light flux is reflected by a half mirror 208, and then radiated via an objective lens 206 onto an observation sample 202. In this case, plural objective lenses 206 are held by a revolver 207 and are selectively placed in light path. The light reflected from the observation sample 202 penetrates the half mirror 208, and a magnified image of the observation sample 202 is formed by a tube lens 209 together with the objective

lens 206. Further, the reflected light is then polarized in the horizontal direction by a reflection mirror 210, and thereby an image of the observation sample 202 by the tube lens 209 is shrunken and photographed by the photographing lens 250 and an image I of the observation sample 202 is formed.

In this case, a display device 230 such as LCD or the like as display means is embedded at the front surface of the scope body 201. While an operating portion 231 that sends various instructions is arranged at the frontal bottom. At the position of the image I of the observation sample, built in is a CCD 223 for outputting the light image formed by the photographing lens 250 as visual signal. To the CCD 233, a signal processing portion 234 that processes the output from the CCD 233 is connected. To this signal processing portion 234, an image recording portion 235 to which an internal memory or an MO (magnetic optical disk) and smart media and the like as a recording medium are attachable, the above display device 230 of an LCD or so, and the operating portion 231 are connected, respectively.

Herein, in FIG. 5, there also illustrated a split prism 251 that branches the light flux in the horizontal direction (paper sheet vertical direction) just below a tube lens 209, a side port 252 that photographs the light flux branched by the split prism

251 by use of a TV camera and the like, and a focusing handle 211 that drives the revolver 207 holding plural objective lenses 206 upward and downward, and thereby changes the relative distance between the observation sample 202 on the stage 203 and the objective lens 206, then thereby sets focus on the observation sample 202.

In the inverted microscope thus constituted, when observation and recording are carried out, motions will be illustrated as follow.

10 Firstly, preview mode (animation observing mode) is set according to the operation of the operating portion 231, and the image is displayed on the display device 230 such as LCD or the like. The objective lens 206a with low magnification is selected by rotating the revolver 207, and the image displayed on the display
15 device 230 such as LCD or the like is focused by rotating the focusing handle 211. Then, it is switched to the objective lens with high magnification 206b by rotating the revolver 207, and when the focus is
20 obscure, it is accurately focused by rotating the focusing handle 211 a little. When an observation position is changed, the position of the observation sample 202 is moved in an XY direction by operating the XY handle (not shown in the figure) of the stage 203,
25 and a desire observation position is moved to the sight of the objective lens 206b.

Then, when the image is recorded in a recording

medium such as MO, smart media or the like, the preview mode is switched to the recording mode by operating the operating portion 231. Then, the display of image recording is presented by photographing operation of the operating portion 231, the image data accumulated in the CCD 233 are recorded in the image recording part 235, and the motion is completed. Further, after completion of the image recording motion, it is automatically switched to the preview mode. The present image is displayed on the display device 230 such as LCD or the like in real time.

Accordingly, according to the present embodiment, since an observatory optical system for observing by the eyepiece is not required, the inverted microscope by which the observation and image recording by a monitor such as LCD or the like can be carried out can be realized by a simple configuration.

FIG. 6 is a view showing the schematic configuration of an inverted microscope according to a third embodiment of the present invention.

In FIG. 6, a stage 303 is arranged to the upper side of a microscope main body 301 (hereinafter, referred to as scope body). An observation sample 302 is mounted on the stage 303. Light flux by a halogen lamp or the like from a light source device 304 is introduced to the scope body 301 through a light projection tube 305. Then, the light flux is reflected

by a half mirror 308, and irradiated on the observation sample 302 through the objective lens 306. In this case, an objective lens 306 are retained by a revolver 307 in a plural number, and arranged in light path in an alternative way. Then, the reflected light from the observation sample 302 transmits the half mirror 308, and the magnified image of the observation sample 302 is formed by the tube lens 309 together with the objective lens 306. Further, the reflected light is polarized to a horizontal direction by a mirror 310, and forms the primary image I1 of the observation sample 302.

Further, scales 312 for measuring the partial size of the observation sample 302 are designed to be able to be inserted at the position of a primary image I1.

Further, the primary image I1 passes a zoom optical system 313, and introduced to two light fluxes of the reflected light to perpendicularly upward direction when the mirror 314 is inserted on the optical path and the passage light to forward direction when the mirror 314 is removed from the optical path, by a mirror 314 of light path-splitting procedure which can be inserted and removed in the light path. The light flux reflected to a perpendicular direction is imaged as a secondary image I2, further, after being relayed by a relay optical system 315, entered in an eyepiece 317 attached at a mirror tube 316, and reaches

at the eyes of an observer to be observed. On the other hand, the passage light to forward direction is contracted by a tube lens 332 which constitutes the imaging optical system, and imaged on a CCD 333.

5 Here, in FIG. 6, a splitting prism for diverging light flux to a horizontal direction (perpendicular direction to space) just under an tube lens 309, a side port 352 for photographing the light flux diverged in a splitting prism 351 by a television camera or the like, and a focusing handle 311 for focusing the
10 observation sample 302 by driving to up and down the revolver 307 in which a plurality of the objective lenses 306 are retained and changing the relative distance between the objective lens 306 and the
15 observation sample 302 on the stage 303, are shown.

 The contraction magnification β of the above-mentioned tube lens 332 is set as follow. In this case, the same range as the range (the size at image face is called the number of sight) of a sample
20 observed by the eyepiece 317 is designed to be able to be pictured. When the number of sight is FN and the diagonal length of imaging element is K, the relation is set as $\beta \doteq K/FN$.

 In front of the scope body 301, a display device
25 330 such as LCD or the like is buried. An operating portion 331 which sends various indications is provided at lower part of the front. Further, a signal

processing part 334 connected with the CCD 333 and
processes the signals from the CCD 333 is connected
with an image recording part 335 to which an internal
memory or an MO (magnetic optical disk) and smart media
5 and the like as a recording medium etc. are attachable,
the fore-mentioned display device 330 such as LCD or
the like, and the operating portion 331, respectively.

In the inverted microscope thus constituted, since
motions at carrying out observation and recording are
10 quite the same as the inverted microscope illustrated
in FIG. 5, illustration is omitted.

Accordingly, when such configuration is made,
a range which is nearly the same range as the display
range by a monitor can be observed by the eyepiece
15 together with the observation by the monitor such as
LCD or the like. Accordingly, the optimum inverted
microscope can be provided to an observer who needs not
only observation by the monitor but also observation by
the eyepiece.

20 Further, in the above-mentioned second and third
embodiments, when the direction of display face of the
display devices 230 and 301 such as LCD or the like
attached in front of the scope bodies 201 and 301 is
designed to be shifted in accordance with the physical
25 status and liking of an observer who faces the scope
bodies 201 and 301, an observation posture which has
less fatigue can be taken.

FIG. 7A and FIG. 7B are views showing an example of a configuration in which the display device 230 such as LCD or the like used for the second embodiment can be moved by swinging to up and down direction. FIG. 7A and FIG. 7B are section views magnified only a portion in which the display device 230 such as LCD or the like in front of the scope body 201 is attached. In FIG. 7A and FIG. 7B, the supporting shaft 402 is provided on a concave portion 201a provided in front of the scope body 201, to a horizontal direction (a vertical direction to space). The display device 230 such as LCD or the like is supported in a condition in which it can be freely moved by swinging to up and down direction while fitting a retaining frame 401 which retains the display device 230 such as LCD or the like, with a supporting shaft 402. The fitting of the retaining frame 401 with the supporting shaft 402 is set so as to generate an appropriate frictional force which copes with a force to lower direction caused by the weight of the display device 230 such as LCD or the like including the retaining frame 401. Accordingly, an observer can freely adjust the angle to up and down direction of the display face of the display device 230 such as LCD or the like holding the retaining frame 401.

FIG. 8A and FIG. 8B are views showing an example of a configuration in which the display device 230 such

as LCD or the like can be moved by swinging to up and
down direction and right and left direction. FIG. 8A
and FIG. 8B are section views which magnified only
a portion in which the display device 230 such as LCD
or the like in front of the scope body 201 is attached.
In FIG. 8A and FIG. 8B, a spherical concave portion
201b is further formed in the concave portion 201a.
The display device 230 such as LCD or the like is
retained by a retaining frame 403. Further, spherical
parts 405 fixed on the back face of the retaining frame
403 through a shaft 404 is fit in the spherical concave
portion 201b. The fitting of the spherical parts 405
with the concave portion 201b is set so as to generate
an appropriate frictional force which copes with a
force to lower direction caused by the weight of the
display device 230 such as LCD or the like including
the retaining frame 403, in like manner as in FIG. 7A
and FIG. 7B. Accordingly, an observer can freely
adjust the angle of the display face of the display
device 230 such LCD or the like, to up and down
direction holding the retaining frame 403.

Further, although a cable was not shown in FIG. 7A
and FIG. 7B and FIG. 8A and FIG. 8B, the cable from the
signal processing part 234 located between the display
face of the display device 230 such LCD or the like and
the scope body 201 is set at an appropriate length so
as to have no load, by the angle adjustment of the

display face as described above.

Further, in the second embodiment, it becomes possible to change the size of the image displayed on the display device 230 such as LCD or the like, namely
5 a so-called electronic zooming, by operation of the operating portion 231. Thus, an observer can freely change observation magnification by operation of the operating portion 231 in front of the scope body 201, without carrying out the switching operation of the
10 objective lens 206 by the rotation of the revolver 207.

Thus, since the angle of the display face of the display device 230 such as LCD or the like can be freely changed, the inverted microscope in which an observation posture which has less fatigue can be taken
15 in accordance with the physical status and liking can be provided.

In the above-mentioned illustration, the display device 230 such as LCD or the like used in the second embodiment is described, but, of course, the
20 configuration shown in FIG. 7A to FIG. 8B can be applied to the display device 330 such as LCD or the like used in the third embodiment.

FIG. 9A and FIG. 12B are configuration views of an inverted microscope which is a fourth embodiment of
25 the present invention.

In the fourth embodiment, although the configuration of the whole inverted microscope is the

same as that of the first embodiment, but differs in illustration in detail concerning, the attachment method of photographing lenses which are used in combination when three image recording devices, namely,
5 a photo photographing device to which a large size camera and a 35 mm film camera can be mounted, a digital camera device in which the observation of animation can be carried out by the display device such as LCD or the like internally stored, and a TV camera
10 are selectively attached on the front port, and the attachment method of the photo photographing device and the digital camera device in the scope body.

In FIG. 9A and FIG. 12B, the same configuration as the first embodiment of FIG. 1 to FIG. 4 is illustrated
15 by bestowing the same codes. In FIG. 9A and FIG. 9B, the scope body 1, the concave fitting part 1a for positioning a photo photographing device 19 provided in front of the scope body 1, a guide member 501 for
20 positioning the photo photographing device 19 fixed at the lower end part of the fore-mentioned concave fitting part 1a and cooperates with the concave fitting part 1a, and a mounting member 502 for retaining the photographing lens unit described later fixed in front of the scope body 1, are shown. (Here, the front port
25 18 in FIG. 1 = the mounting member 502 in a narrow sense, but the front port 18 in FIG. 1 = the mounting member 502 + the concave fitting part 1a + the guide

member 501 in a wide sense, namely, it can be said that the mounting member 502 is one of configuration member of the front port 18). Further, in FIG. 9A and FIG. 9B, the scope body 1, a fixation screw 503 for fixing the photo photographing device 19 fit in the fore-mentioned concave fitting part 1a, a fixation screw 504 for fixing the photographing lens described later fit in the fore-mentioned mounting member 502, and the mirror frame 500 which retains the mirror 14 and is retained at a predetermined position of the scope body 1 in a condition in which it can be inserted and removed against light path, are shown.

FIG. 10A and FIG. 10B show photographing lenses corresponding to three image recording devices, namely, the photo photographing device which can mount a large size camera and a 35 mm film camera, a digital camera device in which the observation of animation can be carried out by the display device such as LCD or the like internally stored, and a TV camera.

FIG. 10A is a view showing photographing lens unit corresponding to the photograph device 19. FIG. 10B is a view showing photographing lens unit corresponding to the digital camera device 29. FIG. 10C is a view showing photographing lens unit corresponding to the TV camera 37. FIG. 10D is a view showing photographing lens unit corresponding to a TV camera which is different from the TV camera 37.

Both of the photographing lens unit corresponding to the photo photographing device 19 of FIG. 10A and the photographing lens unit corresponding to the digital camera device 29 of FIG. 10B are equipped with screws at the outer peripherals of respective lens frames 505 and 506. Further, the lens frames 505 and 506 can be attached on the mounting member 502 by screwing the screws of the outer peripherals of the lens frames 505 and 506 in screw parts 502a of the fore-mentioned mounting member 502.

Both of the photographing lens unit corresponding to the TV camera 37 of FIG. 10C and the photographing lens unit corresponding to a TV camera which is different from the TV camera 37 of FIG. 10D are equipped with V-grooves on the outer peripherals of lens frames 507 and 508. Further, the lens frames 507 and 508 can be attached on the mounting member 502 by inserting the lens frames 507 and 508 in fitting parts 502b of the fore-mentioned mounting member 502, and screwing the fixation screws 504. Further, at one end of the lens frames 507 and 508, camera attachment screw portions 507a and 508a such as C mount or the like for fixing the TV camera are provided.

In the lens frames 505, 506, 507 and 508, lens groups 509, 510, 511 and 512 which have different magnifications respectively are fixed. When photographing is carried out using the photographing

device 19 in combination, the lens group 509 is an optical system having about 3-fold so as to be finally the optimum expanded magnification on a film face. The lens groups 510, 511 and 512 have the optimum contraction magnification according to the digital camera device 29 used in combination and the size of the imaging element such as CCD or the like of the TV camera 37. As the fore-mentioned third embodiment, when the number of sight is FN, the diagonal length of imaging element is K, and the magnification of the lens groups of photographing lens β is set $\beta \approx K/FN$, the range which is nearly the same range as the eyepiece can be imaged.

FIG. 11A to FIG. 11C are views showing the form of the attachment portion of the photo photographing device 19 or the digital camera device 29. In FIG. 11A to FIG. 11C, a main body part 513 of the photo photographing device 19 or the digital camera device 29, an attachment member 514 fixed in the main body part 513, and a dust proof glass 515 fixed on the opening of the main body part 513, are shown. The lower end part of the attachment member 514 has a slope portion 514a corresponding to the fore-mentioned guide member 501. At one side of the upper end of the attachment member 514, a slope portion 514b constituted so that when the fore-mentioned fixation screws 503 are screwed, the fixation screws 503 just contact with

the attachment member 514 and a force pushing the attachment member 514 to the direction of the scope body 1 acts, is formed. Further, the width dimension of the attachment member 514 is equal to the width dimension of the concave fitting part 1a of the scope body 1.

Then, FIG. 12A is a view showing a condition in which the photographing lens of FIG. 10A and the photographing device 19 are attached in the frontal port of the scope body 1. FIG. 12B is a view showing a condition in which the photographing lens of FIG. 10C and the TV camera 37 are attached in the frontal port of the scope body 1.

In FIG. 12A, the photographing device 19 is fixed on the scope body 1. The lens frame 505 of the photographing lens unit of FIG. 10A is screwed in the mounting member 502 fixed in the front of the scope body 1 to be fixed. Then, the width direction of the attachment member 514 is fit in the concave fitting part 1a of the fore-mentioned scope body 1 so that the slope portion 514a of the lower end of the attachment member 514 of the photo photographing device 19 is mounted on the fore-mentioned guide member 501, and the fixation screws 503 are screwed.

Thus, in the present embodiment, when large size devices such as the photo photographing device 19 and the digital camera device 29 are attached, the devices

are not directly fixed on the mounting member 502. The photographing lens is fixed in the mounting member 502, and then the photograph device 19 and the digital camera device 29 are designed to be attached in the frontal part of the scope body 1. Accordingly, a highly accurate and stable combination can be made.

In FIG. 12B, the TV camera 37 is fixed in the scope body 1 as follows. The camera attachment screw portion 507a of the lens frame 507 of the photographing lens unit of FIG. 10C is screwed in the mounting part 37a of the TV camera 37 to be fixed. Then, the lens frame 507 of the photographing lens unit of FIG. 10C in which the TV camera 37 is inserted in the fitting part 502b of the fore-mentioned mounting member 502. Then, after the up and down and left and right directions of the TV camera 37 are adjusted, the fixation screws 504 are screwed. Thus, the TV camera 37 is fixed in the scope body 1 through the photographing lens unit of FIG. 10C.

When the photographing lens unit of FIG. 10D is attached, it can be attached in like manner as in the photographing lens unit of FIG. 10C.

Further, the reason why the fixation method for the mounting member 502 of the photographing lens corresponding to the TV camera 37 was changed against the photographing lens corresponding to the photo photographing device 19 and the digital camera device

29 is for being able to adjust the up and down and left and right directions of the TV camera 37.

As described above, in the present embodiment, when the photo photographing device 19 and the digital camera device 29, and the TV camera 37 are attached on the frontal port, the photographing lenses are attached by different methods, and a proprietary structure for attaching the photograph device 19 and the digital camera device 29 in the scope body is prepared.

Accordingly, even a large size film photographing device and the digital camera device can be attached in the scope body in a high rigidity and good stability.

Further, in case of the photo photographing device 19 and the digital camera device 29, the photographing lens is designed to be also attached in the scope body 1 by being separated from the photo photographing device 19 and the digital camera device 29 as a separate body. Accordingly, the image recording having various magnifications corresponding to the request of an observer can be carried out. Specifically, in case of the present embodiment, the photographing lenses shown in FIG. 10A and FIG. 10B are designed to be used in combination corresponding to the photo photographing device 19 and the digital camera device 29. To the contrary, corresponding to a case of each of the photo photographing device 19 and the digital camera device 29, for example, 2 or more of the photographing lenses

having different magnifications can be also provided.

Then, an inverted microscope according to a fifth embodiment of the present invention will be illustrated.

5 Since the fifth embodiment has the same configuration as that of the third embodiment illustrated in FIG. 6, illustration and the display of drawing are omitted. The fifth embodiment has a characteristic of setting the magnification of the photographing lens 332 at being photographed by CCD 333. Namely, in the
10 present embodiment, it is constituted so that the magnification of the image displayed by the display device 330 such as LCD or the like is equal to the observation magnification at the eyepiece 317.

15 When the magnification of the photographing lens 332 is β' , the diagonal length of CCD 333 is K, the diagonal length of the display device 330 such as LCD or the like is L, and the magnification of the eyepiece 317 is M, an observer can always observe the
20 observation magnification at the eyepiece 317 equal to the magnification of the image displayed by the display device 330 such as LCD or the like by selecting the respective parameters so that the following relation is obtained:

25
$$M = \beta' \cdot L/K \quad (\beta' = M \cdot K/L),$$

therefore he can carry out observation work without any sense of incongruity.

In FIG. 13, when the magnification at the eyepiece 317 is most standard 10-fold, a table of the magnification of the photographing lens 332 for observing at 10-fold equal to the same magnification of the eyepiece 317 in the display device 330 such as LCD or the like, in case of a combination of the sizes of the typical CCD 333 and the display device 330 such as LCD or the like.

Then, an inverted microscope according to a sixth embodiment of the present invention will be illustrated.

Since the sixth embodiment has also the same configuration as that of the third embodiment illustrated in FIG. 6, illustration and the display of drawing are omitted.

In the present embodiment, when the sight number of the eyepiece 317 is FN and the diagonal length of the imaging element 333 such as CCD or the like is K, the magnification β of the photographing lens 332 is set so as to satisfy

$$\beta \doteq K/FN.$$

As shown in FIG. 15 (view in which the operating portion is viewed from the front), switches 601 and 602 for inputting the UP and DOWN of electronic zoom magnification for being able to change display magnification to the display device 330 such as LCD or the like, a display portion 603 for displaying the

electronic zoom magnification, MEMORY switches 604a to
604c for storing the present electronic zoom magnifica-
tion set, and an EXPO switch 605 for recording the
image displayed in the image recording part 336, and
5 the like are arranged in the operating portion 331.

The signal processing part 334 which processes
the output from CCD 333 has a memory for temporarily
preserving image data from CCD 333. When the
electronic zoom magnification is input from the
10 operating portion 331 to be set, the signal processing
part 334 cut out a portion from the image data
temporarily preserved in the memory in accordance with
the electronic zoom magnification, and displays the
range cut out on the display device 330 such as LCD or
15 the like. When the electronic zoom magnification is
0.5-fold, a range of a half of the original data for
the respective vertical and horizontal at around center
is cut out from the image data temporarily preserved in
the memory, and the data is displayed on the display
20 device 330 such as LCD or the like. Thus, the image
having 2-fold of the electronic zoom magnification is
obtained.

In order to store the electronic zoom magnifica-
tion, it is realized by continuously pushing any one of
25 the MEMORY switches 604a to 604c, for example, for a
fixed time or more in a condition in which it is set at
the electronic zoom magnification desired to be stored.

The electronic zoom magnification stored is called out by pushing any one of the MEMORY switches 604a to 604c for a short time, and the image can be displayed at the electronic zoom magnification on the display device 330 such as LCD or the like. Since the processing of cutting out (thin out) a portion from the image data temporarily preserved in the memory is well known, it is omitted here.

As shown in FIG. 14, in the present embodiment, when 2/3 inch-sized CCD was adopted as CCD 333, 0.42-fold is set as the magnification β of the tube lens 332 in order to obtain the same imaging range as the observation range of the number of sight FN = 26.5. Further, a 6-type monitor is assembled as the display device 330 such as LCD or the like.

Then, when the electronic zoom magnification is set at 1.7-fold by the switch 601 which displays the UP of the electronic zoom magnification, the display magnification on the display device 330 such as LCD or the like is $0.42 \times 1.7 \div 0.72$, and it is quite the same as the magnification 0.72 of the tube lens for obtaining the same display magnification as the observation magnification (10-fold) at the eyepiece 317 in FIG. 13.

Accordingly, when it is desired according to the liking of an observer that the area of the image imaged by CCD 333 is nearly equal to the observation area at

the eyepiece 317, the image data imaged by CCD 333 with the tube lens may be displayed in full image as it is, on the display device 330 such as LCD or the like without using electronic zoom. On the other hand, when the image is desired to be observed at the same magnification with the eyepiece 317 on the display device 330 such as LCD or the like, it may be displayed in a magnified display utilizing the electronic zoom. Further, since a plurality of the magnifications (here, until three) of the electronic zoom, it can be observed at an arbitrary magnification on the display device 330 such as LCD or the like. Although not illustrated, when a printer is directly connected with the present inverted microscope and the image temporarily preserved in the signal processing part 334 is printed by the printer, or when the image preserved in the image recording part 335 is printed by an external printer through a recording medium such as smart media or the like, it is easily realized, for example, to coincide the magnification of the print image with the observation magnification (here, 10-fold) at the eyepiece 317 on the output paper of the external printer by empirically setting the electronic zoom magnification corresponding to the printer used and the output paper, utilizing the function of storing a plurality of the fore-mentioned electronic zoom magnification.

An inverted microscope according to a seventh embodiment of the invention is illustrated. Since the total configuration of the inverted microscope related to the seventh embodiment is the same as FIG. 2A and
5 FIG. 2B, illustration and the display of drawing are omitted.

FIG. 16 is a side sectional view of the microscope photograph device applied to the inverted microscope related to the seventh embodiment, and FIG. 17 and
10 FIG. 18 are views in which the lower half side of the microscope photograph device was viewed from upside. FIG. 17 shows a condition in which photograph is carried out by a large size film camera and FIG. 18 shows a condition in which photograph is carried out by
15 a 35 mm film camera, respectively.

In FIG. 16 to FIG. 18, three parts such as a photograph main body 41 which retains the principal part of the photo photographing device, the upper cover 42 fixed on the upper face of the photograph main body
20 41, and a base plate 43 fixed on the photograph main body 41 and constituted so that it covers the photograph main body 41 and the back face of an upper cover 42 are the appearance configuration parts of the microscope photograph device.

25 The photo projection lens part set 44 (photo projection lens) is assembled in the scope body 1, and the imaging flux from the scope body 1 is converted to

an imaging flux having high magnification which is suitable for photo photographing.

Further, optical path switching block 46 is fit to a sliding fantail part of a base part (hereinafter, referred to as the optical path switching base) 45, which leads imaging flux to the large size film camera 20 or the 35 mm camera 21.

On the optical path switching block 46, a projection lens part set 47 for a large size film camera 20 for magnifying and projecting the imaging flux from the scope body 1 to the magnification which is suitable for a large size film camera 20, the reflection mirror 24 for the first large size film camera for polarizing to a slant upper direction the imaging flux which passed the projection lens part set 47 for a large size film camera, a reflection mirror 25 for a 35 mm film camera for polarizing the imaging flux from the scope body 1 to the 35 mm film camera, a first iris plate 49 for stopping the imaging flux from the scope body 1 to the requisite flux diameter to the 35 mm film camera, a second iris plate 50 in which a square hole through which only the flux reflected by the reflection mirror 24 for the first large size film camera passes was provided, and a linking pin 51, are fixed, respectively.

An optical path switching operation lever 52 which is protruded from the side face of the main body 41 to

outside is fixed on the side face of the optical path switching block 46. A positioning mechanism 53 is a ball click and the like for positioning the optical path switching block 46 at either the photograph position by the large size film camera 20 or the photograph position by the 35 mm film camera 21.

When the optical path switching operation lever 52 is pushed in and the optical path switching block 46 is located at the left side viewed from the observer of the microscope (the large size film camera 20 side), the projection lens part set 47 for a large size film camera and the reflection mirror 24 for a large size film camera are inserted in the imaging flux. Then, the optical path switching operation lever 52 is pulled out, and when the optical path switching block 46 is located at the right side viewed from the observer of the microscope (the large size film camera 20 side), the reflection mirror 25 for a 35 mm film camera is inserted in the imaging flux.

An electromagnetic shutter base 54 is fixed on the side face of the optical path switching base 45, and retains an electromagnetic shutter 56 for carrying out a photographing motion through a ring shape elastic member 55. According to the above-mentioned configuration, the electromagnetic shutter 56 is arranged at about the iris position of the imaging flux emitted from the scope body 1.

A mechanical shutter base 57 is equipped with an opening in which the imaging flux toward the large size film camera 20 can pass, at the central part, and fixed on the lower face of the upper cover 42. A mechanical shutter 58 slides along the guide grooves which are formed on the upper face of the mechanical shutter base 57, and is a mechanical shutter which can perfectly block the opening of the fore-mentioned mechanical shutter base 57. A supporting shaft 59 is a supporting shaft fixed on the upper face of the mechanical shutter base 57. A link levers 60 are rotatably retained making the supporting shaft 59 as fulcrum.

These link levers 60 and the mechanical shutter 58 motion in link with the fore-mentioned optical path switching block 46 by action of the fore-mentioned link pins 51.

Then, the aspect of the link motion is illustrated referring to FIG. 19, FIG. 20, FIG. 21A to FIG. 21D.

FIG. 19 is a G-arrow view in which the direction of the mechanical shutter 58 is viewed from the direction of G of FIG. 16. FIG. 19 shows a condition in which the optical path switching block 46 is located at the left side and the photographing by the large size film camera 20 can be carried out. FIG. 20 is a view in which the second iris plate 50 fixed on the upper face of the optical path switching block 46 and in which a square hole in which only the flux reflected

by the reflection mirror 24 for a large size film camera passes is provided is viewed from the G direction.

In FIG. 19, the mechanical shutter base 57 is
5 fixed on the lower face of the upper cover 42. The opening of the upper cover 42 is blocked by attaching the mechanical shutter base 57, and the residual opening is only an opening 57a provided in the mechanical shutter base 57. The mechanical shutter can
10 be freely moved by sliding along the guide grooves formed by a pair of a projection parts 57b.

The long holes 57c which are provided in the mechanical shutter base 57 is a size corresponding to the range in which the link pins 51 fixed on the upper
15 face of the optical path switching block 46 works at switching the light pass.

A groove 60a is formed in one end of the link lever 60. A shutter pin 58a fixed on the upper face of the mechanical shutter 58 is fit in a groove 60a.
20 The another end of the link lever 60 is a contact portion 60b with which the link pin 51 is brought in contact, and the contact portion 60b of the link lever 60 is always brought in contact with the link pin 51 by the clock wise energized force given by the coil spring
25 61 attached on the supporting shaft 59 which rotatably retains the link lever 60.

In FIG. 19, since the optical path switching block

46 is located at the left side, it is in a condition in which the photographing by the large size film camera 20 can be carried out. Accordingly, since the link pin 51 is located at the lower side in FIG. 19, the mechanical shutter 58 is in a condition in which it does not block the opening 57a of the mechanical shutter base 57 by the link lever 60 which is brought in contact with the link pin 51.

At this time, the opening of the mechanical shutter base 57 shown in FIG. 20 is duplicated with the opening 57a of the above-mentioned mechanical shutter base 57, and the imaging flux reflected with the reflection mirror 24 for a large size film camera passes the opening 57a. Further, when the mechanical shutter 58 blocks the opening 57a of the mechanical shutter base 57, the end face of the mechanical shutter 58 hits the stopper pin 57d fixed on the upper face of the mechanical shutter base 57.

Referring to FIG. 21A to FIG. 21D, the aspect of a case in which the link lever 60 and the mechanical shutter 58 motion by linking with the fore-mentioned optical path switching block 46 by the action of the fore-mentioned link pin 51 is illustrated in detail.

FIG. 21A shows a condition in which the mechanical shutter 58 by which the photographing by the large size film camera 20 which is the same as FIG. 19 can be carried out is photographing. FIG. 21B shows

an intermediate condition in which the optical path-switching operation lever 52 is pulled out a little (here, for example, 7.5 mm). FIG. 21C shows an intermediate condition in which the optical path-switching operation lever 52 is further pulled out more slightly (here, for example, 11 mm) than FIG. 21B. FIG. 21D shows a condition in which the optical path-switching operation lever 52 is perfectly (here, for example, 40 mm of whole stroke) pulled out and the photographing by the 35 mm film camera is possible.

When the optical path-switching operation lever 52 is slightly pulled out as shown in FIG. 21B, the second iris plate 50 fixed on the optical path switching block 46 and the link pin 51 move by the pulled-out amount of the optical path switching operation lever 52, and the link lever 60 which is brought in contact with the link pin 51 rotates to a clockwise direction by the energizing force of the coil spring 61. Then, the mechanical shutter 58 moves through the shutter pin 58a fit in the groove 60a of the one end part of the link lever 60, and blocks the portion among the opening 57a of the mechanical shutter base 57.

At this time, since the second iris plate 50 moves also slightly, only the region shown by the oblique line of FIG. 21B is a range in which light can be passed to the first reflection mirror 24 for a large size film camera fixed on the optical path switching

block 46 from an upper direction. The region shown by the reticulated part of FIG. 21B is blocked by the second iris plate 50 even if light is invaded from an upper direction, and is a range in which light does not reach at the first reflection mirror 24 for a large size film camera fixed on the optical path switching block 46.

As shown in FIG. 21C, when the optical path-switching operation lever 52 is pulled out, for example, by 11 mm, the mechanical shutter 58 moves further, and blocks perfectly the opening 57a of the mechanical shutter base 57. Accordingly, the light invaded from an upper direction cannot reach at the direction of the optical path switching block 46.

As shown in FIG. 21D, even if the optical path switching operation lever 52 is perfectly pulled out, the mechanical shutter 58 is yet in a condition in which it blocks perfectly the opening 57a of the mechanical shutter base 57, and the light invaded from an upper direction cannot reach at the direction of the inner optical path switching block 46.

Thus, since the light path is directly blocked by the action of the link lever with the mechanical shutter 58 by only pulling out the inner optical path switching block 46 from the condition as shown in FIG. 21A in which the photographing by the large size film camera 20 can be carried out, the light path is

blocked to the utmost except a requisite time.

5 If the large size film camera 20 is removed by the
observer of the microscope in the condition of FIG. 21A
in which the photographing by the large size film
camera 20 can be carried out and in the intermediate
condition of FIG. 21B, light from outside invades into
the first reflection mirror 24 for a large size film
camera fixed on the optical path switching block 46
through the opening 57a of the mechanical shutter base
10 57. However, the light from outside which invaded is
reflected by the first reflection mirror 24 for a large
size film camera, and all of the light reaches to the
direction of the electromagnetic shutter 56 through
the projection lens part set 27 for a large size film
15 camera, therefore it does not reach to the direction of
the 35 mm film camera 21 at all.

When the 35 mm film camera 21 is suddenly removed
by the observer of the microscope, the light from
outside invades from the 35 mm film camera 21 side.
20 However, if the optical path switching operation lever
52 is pulled out and in a condition in which the
photographing by the 35 mm film camera 21 can be
carried out, the mechanical shutter 58 perfectly blocks
the opening 57a of the mechanical shutter base 57,
25 therefore the light from outside does not reach to the
direction of the large size film camera 20 at all.

Further, if the optical path-switching operation

lever 52 is pushed in, the external light which invaded from the 35 mm camera 21 side does not reach to the direction of the large size film camera 20 at all because it is wholly reflected to the direction of the electromagnetic shutter base 54 by the reflection mirror 25 for a 35 mm film camera.

When the optical path switching operation lever 52 is situated at an intermediate position, the external light which invaded from the 35 mm film camera 21 side does not yet reach to the direction of the large size film camera 20 at all because it is wholly reflected to the direction of the electromagnetic shutter base 54 by the reflection mirror 25 for a 35 mm film camera.

Returning again to FIG. 16, FIG. 17 and FIG. 18, the photograph device will be illustrated.

When the optical path switching operation lever 52 is pushed in as shown in FIG. 17, the imaging flux reflected by the first reflection mirror 24 for a large size film camera fixed on the inner optical path switching block 46 passes the opening 57a of the mechanical shutter base 57 without being blocked by the mechanical shutter 58. Then, the light flux which passed the opening 57a becomes the imaging flux to obliquely forward by being reflected by the second reflection mirror 26 for a large size film camera fixed on the uppermost part of the upper cover 42 through the mirror fixation member 62 and the third reflection

mirror 27 for a large size film camera fixed on the
back face side of the upper cover 42. Then, it passes
the dust proof glass 63 fixed in front of the said
upper cover 42 of the imaging flux and imaged on the
5 large size face of the large size film camera 20.

When the optical path switching operation lever 52
is pulled out as shown in FIG. 18, the imaging flux
reflected by the first reflection mirror 25 for a 35 mm
film camera fixed on the inner optical path switching
10 block 46 passes the opening of the 35 mm film camera
mount 64 fixed on the side face of the photograph main
body 41, and imaged on the film face of the 35 mm film
camera 21.

When the electromagnetic shutter 56 and the
15 mechanical shutter 58 are in a closed condition, the
first space completely closed by the large size film
camera 20 and the mechanical shutter 58 and the second
space completely closed by the electromagnetic shutter
56, the mechanical shutter 58 and the 35 mm film
20 camera 21.

Further, although display by the drawing is
omitted in FIG. 16, the repulsive mirror part set 65
in which the portion of around the center among the
imaging flux is reflected in front of photographing and
25 evacuated from the imaging flux to pass as it is, is
arranged between the photograph projection lens 27 and
the electromagnetic shutter 56 as shown in FIG. 17 and

FIG. 18.

The imaging flux reflected by the repulsive mirror part set 65 is focused by the projection lens part set 66 for measurement, and enter into the light measurement element 68 such as a photo-diode or the like attached on the attachment member 67 fixed on the projection part 43a of the base plate 43.

The dust proof glass 69 is fixed at the opening 43b of the base plate 43 to which the imaging flux from the scope body 1 firstly enters into the photograph device. Further, the fixation member 70 for attaching the photo photographing device in the scope body 1 is fixed at the back face side of the base plate 43.

The cover plate 71 is fixed on the bottom face of the photograph main body 41. The control substrate 72 on which CPU for controlling the respective parts of the photo photographing device 28 such as the electromagnetic shutter 56 or the like is mounted is attached on the upper face of the cover plate 71.

Further, two positions of the optical path switching block 46, namely, two position detection sensors 73a and 73b such as a photo-interrupter and the like corresponding to the position at which the photographing by the large size film camera 20 can be carried out and the position at which the photographing by the 35 mm film camera 21 can be carried out, are attached at the optical path switching base 45.

The two position detection sensors 73a and 73b cooperate with the sensor plate 74 fixed in the optical path switching block 46, and the two positions of the optical path switching block 46 can be detected.

5 Further, when the optical path switching block 46 is located at an intermediate position which is not the position at which the above-mentioned photographing by the large size film camera 20 can be carried out and the position at which the photographing by the 35 mm
10 film camera 21 can be carried out, for example, in a condition shown in FIG. 21B and FIG. 21C, either of two position detection sensors 73a and 73b of the photo-interrupter and the like do not detect the optical path switching block 46, therefore it can be
15 judged that the optical path switching block 46 is located at an intermediate position.

FIG. 22A and FIG. 22B are views showing the relation of the two position detection sensors 73a and 73b with the optical path switching block 46. FIG. 22A
20 shows a condition in which the optical path switching block 46 is located at the left side viewed from the frontal side of the photo-photographing device (the large size film camera 20 side) and the imaging flux is reflected by the first reflection mirror 24 for a large
25 size film camera. In this case, the detection sensor 73a is blocked by the left end side of the sensor plate 74 fixed in the optical path switching block 46, and

the optical path switching block 46 is detected.

FIG. 22B shows a condition in which the optical path switching block 46 is located at the right side viewed from the frontal side of the photo photographing device 28 (the large size film camera 20 side) and the imaging flux is reflected by the reflection mirror 25 for a 35 mm film camera. In this case, the detection sensor 73b is blocked by the right end side of the sensor plate 74 fixed in the optical path switching block 46, and the optical path switching block 46 is detected.

FIG. 23 is a block view showing a schematic configuration of the electric system containing the position detection sensors 73a and 73b and the electromagnetic shutter 56. Either of the respective position detection sensors 73a and 73b is connected with the control substrate 72, and it is designed to be able to watch whether the optical path switching block 46 is located at the position at which the photographing by the large size film camera 20 can be carried out, or at the position at which the photographing by the 35 mm film camera 21 can be carried out, or at an intermediate position being neither of them.

The motor for driving M is a motor for driving the repulsive mirror part set 65, the motor for driving M and the measurement element 68 such as a photo-diode and the like are also connected with the control

substrate 72, and the output from the measurement element 68 is usually monitored by the control substrate 72.

5 A controller HS is a controller by which the observer of the microscope carries out the input operation for photographing operation and various settings, and the signals input from the controller HS are transmitted to the control substrate 72 which is connected. The electromagnetic shutter 56 is connected
10 with the control substrate 72 in order to control the opening and closing condition by display from the control substrate 72.

The motion of the photo photographing device related to the seventh embodiment constituted as above
15 is illustrate.

The observer of the microscope operates the optical path switching operation lever 52 firstly, and selects whether the photographing by the large size film camera 20 is carried out, or the photographing by
20 the 35 mm film camera 21 is carried out.

When the photographing by the large size film camera 20 is carried out, the optical path-switching operation lever 52 is pushed in and when the photographing by the 35 mm film camera 21 is carried out,
25 the optical path-switching operation lever 52 is pulled out. Thus, a light path which can introduce the imaging flux required for photographing the photo of

the observation sample 2 to the large size film camera 20 or the 35 mm film camera 21 is secured. When the photographing by the 35 mm film camera 21 or the 35 mm film camera 21 is in a possible condition by pushing in or pulling out the optical path switching operation lever 52, it is confirmed that the control substrate 72 is in a condition in which the photographing can be carried out according to the signals from the position detection sensors 73a and 73b, and it is in a waiting condition.

On the other hand, since the repulsive mirror part set 65 is in condition in which the mirror is always inserted in the light path at a usual time until the photographing motion is carried out, the portion of the imaging light flux enters into the light measurement element 68, the brightness of the image of the observation sample 2 is converted to electric signals, and the signals are transmitted to the control substrate 72.

The photographing conditions such as an optimum exposure time and the like are determined by inputting the output signals from the light measurement element 68 and the signals from the position detection sensors 73a and 73b.

A series of these motions are repeatedly carried out until the observer of the microscope pushes the photographing switch of the controller 85. When the

brightness of the observation image is changed by changing the observation site operating the XY handle (not shown in the figure) of stage 3 of the observation sample 2, the photographing conditions such as an optimum exposure time and the like are changed in accordance with it.

When the site and the magnification photographed are determined and the observer of the microscope pushes the photographing switch of the controller HS, the photographing motion is started in accordance with the photographing conditions such as an optimum exposure time and the like determined just before the photographing switch is pushed. Firstly, an display is presented from the control substrate 72 to the driving motor M, and the mirror of the repulsive mirror part set 65 is retreated from the light path. When the mirror of the repulsive mirror part set 65 is retreated from the light path, an display for releasing the electromagnetic shutter 56 by the optimum exposure time determined is presented at the same time. The imaging flux passes during the electromagnetic shutter 56 is photographing.

When the optical path switching operation lever 52 is pushed in, the imaging flux passes the projection lens part set 47 for a large size film camera, is reflected by the first reflection mirror 24 for a large size film camera, and passes the opening 57a of the

mechanical shutter base 57 which is not blocked by the mechanical shutter 58. Then, the light flux which passed the opening 57a is reflected by the second reflection mirror 26 for a large size film camera and the third reflection mirror 27 for a large size film camera, further passes the dust proof glass 63, and reaches at the large size film surface of the large size film camera 20. Thus, the photographing by the large size film camera 20 is completed under the determined photographing conditions such as an optimum exposure time and the like.

When the optical path switching operation lever 52 is pulled out, the imaging flux is reflected by the first reflection mirror 25 for a 35 mm film camera, passes the opening of the 35 mm film camera mount 64, and reaches at the 35 mm film surface of the 35 mm film camera 21. Thus, the photographing by the 35 mm film camera 21 is completed under the determined photographing conditions such as an optimum exposure time and the like.

Thus, according to the seventh embodiment, in the microscope photo photographing device which can mount the large size film camera 20 and the 35 mm film camera 21 at the same time, the light leak to one camera in a condition in which another camera 20 or 21 is not mounted can be surely prevented, and an error operation by the optical path switching operation can be

prevented.

When the electromagnetic shutter 56 and the mechanical shutter 58 are in a closed condition, it is constituted that the first space completely closed by the large size film camera 20 and the mechanical shutter 58 and the second space completely closed by the electromagnetic shutter 56, the mechanical shutter 58 and the 35 mm film camera 21 are designed to be formed. Accordingly, the light path of the side which is not really used for the photographing among the large size film camera 20 or the 35 mm film camera 21 is blocked by the mechanical shutter 58 in link with the optical path switching block 46, the imaging flux is introduced only to another camera 20 or 21, and an unnecessary stray light to the one camera 20 or 21 desired to photograph can be cut. Thus, the unnecessary stray light is not generated in the inner part of the photographing device 28, and good photographing can be carried out.

Further, since the space which contains the large size film camera 20 and the space which contains the 35 mm film camera 21 are perfectly separated, even if either of the large size film camera 20 or the space which contains the 35 mm film camera 21 is removed, a structure in which the external light from the removed camera side does not reach at another camera can be realized, and the leak light to one camera caused by

a sudden removal of another camera can be prevented.

Accordingly, when the large size film camera 20 or the 35 mm film camera 21 are removed by the observer of the microscope, the external light which invades in
5 from the position of the large size film camera 20 or the position of the 35 mm film camera 21 does not reach to the direction of the large size film camera 20 or the 35 mm film camera 21 at all even if the optical path switching operation lever 52 is in any condition,
10 therefore the 35 mm film or the large size film is not suddenly exposed to light, and it has an advantage that no mistake in photographing does not occur at all.

Further, when the optical path switching block 46 is located at an intermediate position other than the
15 two positions, namely, the position at which the photographing by the large size film camera 20 can be carried out and the position at which the photographing by the 35 mm film camera 21 can be carried out, it is judged by the signals from the two position detection
20 sensors 73a and 73b that the control substrate 72 is not in a condition in which it can be photographed, therefore the photographing operation is not carried out by mistake, and it has also an advantage that a mistake of generating a defect at the portion of the
25 sight does not occur at all. Namely, it is possible to realize the prevention of generating a defect at the portion of the photographing sight.

The present invention is not limited to the above-mentioned embodiment. For example, in the above-mentioned embodiment, a case of mounting the large size film camera and the 35 mm film camera was illustrated, but it is a matter of course that a case of mounting a camera other than these cameras exhibits also the same effect. It can be carried out by variously changing additionally.

As described above, the inverted microscope related to the present invention is constituted as described below.

(1) The inverted microscope according to the present invention is characterized by comprising: an image output port that forms an image of an observation sample to the external surface facing to an observer, at the front side of a microscope main body, below an observation tube to which eyepieces are attached, wherein photographing devices configured that one of at least two kinds of photographing devices is selectively attachable/detachable to the image output port. Further, the inverted microscope according to the present invention is characterized in that the at least two kinds of photographing devices include: a photographing device that exposes and forms the image of the observation sample onto a film surface thereof; a TV camera that photographs the image of the observation sample by a photographing element thereof and outputs

image data thereof; and a digital camera device that photographs the image of the observation sample and can record the image data as a still image into a recording medium..

5 The photo photographing devices such as a large size film camera and a 35 mm film camera and the preferable image recording devices such as a TV camera, a digital camera, and the like can be efficiently used in combination according to the requirement of the
10 observer of a microscope.

(2) In (1), the inverted microscope according to the present invention is characterized in that the image formed on the image output port is an image that is reflected once by a reflection member in a light
15 path from the observation sample to the image output port, and the image formed on the film surface of the photographing device is a front image that is reflected even-numbered times by a reflection member in the light
20 path from the observation sample to the film surface, by providing the reflection member in the photographing device and generates odd-numbered times of reflections in the light path from the image output port to the film surface.

Since an image formed on the film surface of the
25 large size film camera and the 35 mm film camera is made as a front image (an image having the same direction as the surface of a sample was observed as it

was) while suppressing the light intensity loss and deterioration of image quality caused by the reflection of imaging flux in the main body of a microscope (scope body) to minimum, it is possible to faithfully record
5 the magnified image of the tissue of a metal or the like.

(3) The inverted microscope according to the present invention is characterized comprising: an image forming optical system including objective lenses
10 arranged below an observation sample placed on a stage of a microscope main body; an optical element which forms an image of the observation sample at the position where an image forming light flux obtained by the image forming optical system is polarized to
15 an observer side from the optical axis of the objective lens; photographing means for photographing an image of the observation sample; an image recording section configured to record image signals photographed by the photographing means; and display means attached to the
20 surface facing to the observer at the front of the microscope main body, for displaying images photographed by the photographing means.

A monitor observation with less fatigue is realized by providing a display device such as LCD
25 or the like which displays an image photographed by an imaging element, in front of the main body of a microscope, and the image recording can be easily

carried out. Further, since the observation optical system for observation by an eyepiece is not required, an inverted microscope which can carry out the observation by a monitor such as LCD or the like and the image recording can be realized by a simple configuration.

(4) In (3), the inverted microscope according to the present invention is characterized by further comprising: a light path splitting means for splitting the light path of an image of an observation sample formed by the image forming optical system; a relay optical system for guiding to an eyepiece the light flux from an observation sample of one light path split by the light path splitting means; and a photographing optical system set to a specified contraction magnification for guiding to the photographing means the light flux from an observation sample of the other light path split by the light path splitting means.

Both of the observation optical system for observation by an eyepiece and the imaging optical system with a low magnification suitable for the size of the imaging element can be realized by a simple configuration. Further, since a range which is nearly the same range as an display range by a monitor can be observed by the eyepiece together with the observation by the monitor such as LCD or the like, an inverted microscope being optimum to an observer who needs not

only the observation by a monitor but also the observation by an eyepiece can be provided.

(5) In (3) or (4), the inverted microscope according to the present invention is characterized in that the display angle of the display means is variable.

Since the angle of the display face of a monitor such LCD or the like can be freely changed, an inverted microscope by which an observation posture with less fatigue can be taken in according with the physical status and liking of an observer can be provided.

(6) In (1) or (2), the inverted microscope according to the present invention is characterized in that the image of the observation sample is formed at the position protruded by a specified distance from the image output port, and when attaching one of the photographing device, the TV camera, and the digital camera device, a photographing lens unit corresponding to any of the photographing device to the image output port, the TV camera, and the digital camera device, among plural photographing lens units having different photographing magnifications, is assembled into the end surface portion of the image output port in an attachable/detachable manner.

Since an tube lens with an appropriate magnification can be easily combined in accordance with a image recording device and a photographing lens can be attached in the scope body in a separate body from a

photo photographing device and a digital camera device,
even a large scale photo photographing device and a
digital camera device can be attached in the scope body
in a high rigidity and good stability, and as a result,
5 a good image recording without image deviation can be
realized.

(7) In (6), the inverted microscope according
to the present invention is characterized by further
comprising plural photographing lens units having
10 different photographing magnifications respectively in
accordance with the photographing device, the digital
camera device, and the TV camera, and one of the plural
photographing lens units is assembled therein according
to the kind of the photographing device, the TV camera,
15 and the digital camera device.

A image recording with various imaging
magnification can be carried out corresponding to the
wide requirement of an observer irrespective of the
kind of a photo photographing device and image
20 recording devices such as a digital camera device, a TV
camera and the like.

(8) In (6) or (7), the inverted microscope
according to the present invention is characterized in
that the contraction magnification of the photographing
25 system is so set that the magnification of the image of
the observation sample displayed by the display means
should be equal to the magnification of the image of

the observation sample observed by the eyepieces.

An observer can always carry out an observation in which an observation magnification at an eyepiece is equal to the magnification of an image displayed by a display procedure, and can carry out an observation work without any trouble.

(9) In (6) or (7), the inverted microscope according to the present invention is characterized in that when displaying the image photographed by the photographing means by the display means, a signal processing portion having an electronic zoom function for magnifying the image by an optional magnification is arranged, and the contraction magnification of the photographing optical system (β) is made so that the area of the image photographed by the photographing means should be almost equal to the area observed by the eyepieces ($\beta \doteq K/FN$, when the width across of the photographing element is set as K , and the number of views of the eyepieces is set as FN), and the magnification of the electronic zoom is made variable, thereby the magnification of the image of the observation sample displayed by the display means can be made equal to the magnification of the image of the observation sample observed by the eyepieces.

While realizing the taking-in of maximum range in which the range of an image imaged by the fore-mentioned imaging procedure is nearly the same

observation range as that of the fore-mentioned
eyepiece, the observation at the same magnification as
the eyepiece can be also carried out by displaying in
magnification on a display procedure utilizing an
5 electronic zoom, according to the liking of an observer.

(10) In (6) or (7), the inverted microscope
according to the present invention is characterized by
further comprising: means for storing plural magnifica-
tions of the image of the observation sample displayed
10 by the display means changed by the electronic zoom
function; and means for setting the magnification of
the image of the observation sample displayed by the
display means to an optional magnification.

An observation at an electronic zoom magnification
15 stored using a display procedure can be easily carried
out.

Further, according to the above-mentioned
respective inverted microscope, it comes to be possible
to copy micro-scale and the like and to record the
20 image whose magnification was changed by zoom in all of
the fore-mentioned image recording device, and it is
very preferable in working.

Additional advantages and modifications will
readily occur to those skilled in the art. Therefore,
25 the invention in its broader aspects is not limited to
the specific details and representative embodiments
shown and described herein. Accordingly, various

modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2